



注：對絞“○○○○”

測試條件：

1. 100%測試開路.短路.錯線
2. 導通阻抗：2Ω/Max
3. 絕緣阻抗：20MΩ/Min
4. 測試電壓：300V DC

WIRE RUN LIST

P1	P2	P1	P2
1	1	23	23
2	2	24	24
3	3	25	25
4	4	26	26
5	5	27	27
6	6	28	28
7	7	29	29
8	8	30	30
9	9	31	31
10	10	32	32
11	11	33	33
12	12	34	34
13	13	35	35
14	14	36	36
15	15	37	37
16	16	38	38
17	17	39	39
18	18	40	40
19	19		
20	20		
21	21		
22	22		

5	1	超薄醋酸膠布	W=15
4	1	導電膠布	W=15
		UL10064#32AWG OD=0.38	紅 (RED)
		UL10064#32AWG OD=0.38	黑 (BLACK)
3		UL10064#32AWG OD=0.38	白 (WHITE)
		UL10064#32AWG OD=0.38	藍 (BLUE)
1	2	CONNECTOR 40P	CVS-H-40
NO	QTY	NAME	SPECIFICATION

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PJECTION

照片框

ORDER INFORMATION

CVSX2-404032-M4N-LF

SERIES

LEADFREE

102mm

MALE TO MALE

32 AWG

40 TO 40 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: