



A	線色	B
1	紅	1
2	紅	2
3	紅	3
4	紅	4
5	紅	5
6	紅	6
7	紅	7
對絞	8 白	8
對絞	9 綠	9
10	紅	10
對絞	11 白	11
對絞	12 綠	12
13	紅	13
對絞	14 白	14
對絞	15 綠	15
16	紅	16
對絞	17 白	17
對絞	18 綠	18
19	紅	19
對絞	20 白	20
對絞	21 綠	21

A	線色	B
22	紅	22
23	紅	23
24	紅	24
25	紅	25
26	紅	26
27	紅	27
28	紅	28
20	紅	20
29	紅	29
30	紅	30
31	紅	31
32	紅	32
33	紅	33
34	紅	34
35	紅	35
36	紅	36
37	紅	37
38	紅	38
39	紅	39
40	紅	40

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL10064 #34 紅	30PCS	E108485
2	WIRE:	UL10064 #34 白	5PCS	E108485
3	WIRE:	UL10064 #34 綠	5PCS	E108485
4	HOUSING:	PITCH 0.50mm CVS 40P	2PCS	
5				
6				
7				
8				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

CVSX2-404034-M4N-LF

SERIES

LEADFREE

100mm

MALE TO MALE

34 AWG

40 TO 40 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y