



Specifications

rating :

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

7	Strain Boot			1
6	Terminals	Brass	Silver Ptd.	8
5	8P270 Housing	ABS		1
4	Setscrew	Steel	Nickel Ptd.	1
3	T Holder	Steel	Nickel Ptd.	1
2	Cap	Zn Alloy	Nickel Ptd.	1
1	Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

DASM-PA-08-LF

SERIES T T LEADFREE
08 WAY
ASSEMBLY
MALE

DESCRIPTION: