



PIN OUT:

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
shell	drain
	shell

ITEM	PART NO.	DESCRIPTION	Q' TY
1	DS-PS-09	D-SUB SOLDER TYPE 9WAYS MALE INSULATION BLUE	1
2	DS-SS-09	D-SUB SOLDER TYPE 9WAYS FEMALE INSULATION BLUE	1
3	808A-4*36.5A	THREAD 4*36.5MM SCREW	4
4	810A-9C28B5.0WH	UL 2464 28AWG*9C+ADB OD:5.0MM COLOR WHITE	
5	827-PVC-45P-WH	45P PVC MOLDING COLOR WHITE	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

DBX2-090928-E1M8-LF

SERIES

LEADFREE

1800mm
MALE TO FEMALE
28 AWG
09 TO 09 WAY

DESCRIPTION: Round Cable Assembly