




PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.10	G±0.25	H±0.05
DC-S-09	30.81	24.99	16.35	7.90	17.50	2.84	12.55	2.77
DC-S-15	39.25	33.32	24.51	7.90	17.50	2.84	12.55	2.77
DC-S-25	53.04	47.04	38.35	7.90	17.50	2.84	12.55	2.77
DC-S-37	69.32	63.50	54.84	7.90	17.50	2.84	12.55	2.77

Note:

1. Material:

- 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: Copper alloy,t=0.20mm
- 1.3 Shell: Spcc,t=0.30mm

2. Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min.
- 2.5 Total mating force: 7.0 Kgf Max.
- 2.6 Total unmating force: 1.5 Kgf Min.
- 2.7 Temperature range: -55°C~85°C

8	Back-shell			
7	Front-shell			
6	Clip			No finish
5	Contact			Selective Au plated on mating area
4	Contact			
3	Contact			
2	Contact			
1	Housing			Black
No.	Name	Q'ty	Part No.	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

照片框

ORDER INFORMATION

DC-S-xx-LF
SERIES | LEADFREE
09~37 WAY
FEMALE

DESCRIPTION: D-SUB CRIMP CONNECTOR