



ELECTRONIC TEST:

1. 100% TEST, (Open, Short, Miss Wire).
2. Conduct Resistance: 5Ω /max.
3. Insulation Resistance: $10M\Omega$ /min.
4. Hi-Pot: 300v dc/10ms.

PIN OUTS

P1	P2
1	1 RED(红)
2	2 BLACK(黑)

包装方式: 100PCS/袋.

3	PVC 45P 黑色外模	KG/K
2	DC5521 音叉公头 2PIN 镀镍	1 PCS
1	UL 2464 24AWG*2C OD: 3.0mm 外被黑色 L=100MM	1 PCS
ITEM	STANDARD SPECIFICATION	Q' TY UNIT

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

TOLERANCES ARE

X.±
.X±
.XX±
.XXX±
ANG±

PPOJECTION

照片框

ORDER INFORMATION

DCX1-552124-M10C-LF

SERIES

LEADFREE

100mm

MALE

24 AWG

5.5x2.1mm

DESCRIPTION: DC5521 音叉公头 T0 尾端脱皮15MM 镀锡7MM CABLE BLACK L=100MM