


Recomended PCB Layout

Specifications

Contact Resistance: $\approx 30m$ max. at DC
100mA

Insulator Resistance: 1000M min. at DC
500V

Current Rating: 5 AMP

Dielectric Withstanding

Voltage: AC 1000V For 1 minute

Operating Temperature: $-55^{\circ}C \sim +105^{\circ}C$

Contact: Brass

Housing: PBT & 30% Glass Fiber (UL
94V-0)

Dimension

Positon	A	B	C
9	16.92	24.99	30.81
15	25.50	33.32	39.14
25	38.96	47.04	53.04
37	55.42	63.50	69.32

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. $\pm$
.X ± 0.10
.XX ± 0.05
.XXX $\pm$
ANG $\pm$



ORDER INFORMATION

DDM-P-xx-LF
SERIES | LEADFREE
09~37WAY
MALE

DESCRIPTION: D-SUB DIP STRAIGHT TYPE W/O METAL REAT SHELL