



# PIN OUT

P1		P2	COLOR
1	—	1	RED
2	—	2	RED
3	—	3	BLACK
4	—	4	BLACK
5	⌵	5	BLUE
6	⌶	6	WHITE
7	—	7	BLACK
8	⌵	8	BLUE
9	⌶	9	WHITE
10	—	10	BLACK
11	⌵	11	BLUE
12	⌶	12	WHITE
13	—	13	BLACK
14	⌵	14	BLUE
15	⌶	15	WHITE
16	—	16	BLACK
17	⌵	17	BLUE
18	⌶	18	WHITE
19	—	19	BLACK
20	—	20	×

1. P1 : 1.0mm PITCH CRIMP TERMINAL AND HOUSING DF19-H-20 or EQUIVALENT
2. P2 : 1.25mm PITCH CRIMP TERMINAL AND HOUSING DF14-H-20 or EQUIVALENT
3. P3 : EXPANABLE SLEEVING IN COPPER BRAID ACETATE CLOTH TAPE OVER OUTSIDE COLOR=BLACK
4. WIRE IS UL(1571) 28AWG 80°C 30V PVC JACKET

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

## ORDER INFORMATION

DF14DF19-202028TB1-F20C-LF

SERIES

LEADFREE  
200mm  
FEMALE TO FEMALE  
TUBE  
28 AWG  
20 TO 20 PIN

DESCRIPTION: WIRE HARNESS