





Recommended Module Layout



P.C.B. layout

MATERIALS

- * Body : Liquid Crystal Polstal (L.C.P.) UL (94V-0)
- * Contact : Copper alloy
- * Contact plated : gold over niket (40-60u")or tin plating
- * Latch : Nylon 66 UL (94 V-0)

SPECIFICATION

- * Contact curret rating : 1 AMP
- * Conact resistance : 30 Milli OHMS Max.
- * Insulation resistance : 10,000 megooohms Min. initial
- * Operating temperature : -55°C to +105°C
- * Dielectric Withstanding Voltage : 1.0KVAC
- * Capacitance : 1pf Max.
- * Durability : 25 cycle Min.
- * Contact engaging force : 110 g Max. per conact,initial
- * Contact separating force : 40 g Min. per contact,initial

RoHS Compliant

TOLERANCES ARE

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.35

UNIT / mm

SCALE 1 : 1

.XX ± 0.25

DATE

.XXX ± 0.05

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

DIM1-AZ-240V15-LF

SERIES LEADFREE

1.5V

240 WAY

CLIP

SLANT DIP

DESCRIPTION: DDR3-240P 1.0mm pitch 25 degree type

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com