





03,05Pin



04,05B,06Pin



07,08Pin



SPECIFICATION :

Insulation Resistance : 100M OHM Min. at 500V D.C.

Dielectric Strength : 1,000V A.C. / 1 Minute.

Contact Resistance : 20m OHM Max.

Rating : 100V A.C. 2A

ARRANGEMENT OF CONTACTS							
(DEGREE)	(180°)	(210°)	(180°)	(240°)	(240°)	(270°)	(270°)
NO. OF CONTACTS	3	4	5	5	6	7	8
MODEL NO.	DJ-S5-03	DJ-S5-04	DJ-S5-05	DJ-S5-05B	DJ-S5-06	DJ-S5-07	DJ-S5-08
HOLE LAYOUT							

RoHS Compliant

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1


DATE

SIZE A4

PPOJECTION

TOLERANCES ARE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

DJ-S5-xx-LF
SERIES | LEADFREE
03~08WAY
5.0mm
ALL PLASTIC

DESCRIPTION: