

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 5 Amperes.

Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.

Insulation Resistance: 5000 MΩohms Minimum

Contact Resistance: 25 Milliohms Maximum.

Operating Temperature: -55°C to +105°C.

MECHANICAL CHARACTERISTICS:

Contact Insertion Force: 341 g. Maximum.

Contact Separation Force: 21 g. Minimum.

MATERIALS:

Contacts: Brass.


Insulator: PBT UL 94V-0 Rated.

Shell: Cold Roller Steel.


FINISHES:

Contact: Gold Flash.

Shell: Nickel Plated.



RECOMMENDED P.C.B LAYOUT



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

DRB1-EN15-0909-LF

SERIES

LEADFREE

09 MALE TO 09 FEMALE

SPACING 15.88mm

NUT

MALE TO FEMALE

DESCRIPTION: D-SUB CONNECTOR 9 MALE/9 FEMALE DUAL PORT