





PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10
DS-PSJ-09	30.81	24.99	16.92	8.38	15.30		12.55	2.77	2.84
DS-PSJ-15	39.25	33.32	25.25	8.38	15.30		12.55	2.77	2.84
DS-PSJ-25	53.04	47.04	38.96	8.38	15.30		12.55	2.77	2.84
DS-PSJ-37	69.50	63.50	55.42	8.38	15.30		12.55	2.77	2.84

Note:

1.Material:

- 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: Copper alloy,t=0.20mm
- 1.3 Shell: Spcc,t=0.30mm

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min.
- 2.5 Total mating force: 7.0 Kgf Max.
- 2.6 Total unmating force: 1.5 Kgf Min.
- 2.7 Temperature range: -55°C~85°C

8	Back-shell	1		
7	Front-shell	1		
6	Clip	1		No finish
5	Contact	4		Selective Au plated on mating area
4	Contact	4		
3	Contact	4		
2	Contact	4		
1	Housing	1		Black
No.	Name	Q'ty	Part No.	Finish

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

TOLERANCES ARE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

DS-PSJ-xx-LF
SERIES | LEADFREE
09~37WAY
JACKSCRW
SEMI GOLD
MALE

DESCRIPTION: