



Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Mating force: 9.0 Kgf Max.
6. Unmating force: 3.2 Kgf Min.
7. Temperature range: -55°C~+105°C

9PIN	A	30.80±0.25	B	25.00±0.25	C	16.92±0.25
15PIN		39.20±0.25		33.32±0.25		25.25±0.25
25PIN		53.05±0.25		47.04±0.25		38.96±0.25
37PIN		69.40±0.25		63.50±0.25		55.42±0.25

7	6.0 Nut	2	Brass	H4.75*6.0	80u"min Nickel Plated
6	8.0 Nut	2	Brass	H4.75*8.0	80u"min Nickel Plated
5	3B Nut	2	Brass	H4.75*4.75	80u"min Nickel Plated
4	Back-shell	1	Cold Rolled Steel	T=0.40mm	Cu:40u"min. 80u"min Tin Plated
3	Front-shell	1	Cold Rolled Steel	T=0.40mm	Cu:40u"min. 80u"min Nickel Plated
2	Contact	9 ~ 37	Brass	T=0.20mm	Contact area:0.8u"min Gold Plated over 40u"Nickel min. Solder area:80u"min Tin Plated over 40u"Nickel min.
1	Housing	1	P.B.T	UL 94-V0	Black/Blue/White
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

J	前鉚型(不通孔)	N	后鉚型(通孔)

照片框

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

ORDER INFORMATION

DS-PSx-xx-LF
SERIES T LEADFREE
09~37 WAY
N:NUT
J:JACKSCREW
SOLDER
MALE

DESCRIPTION: D-SUB 9~37PIN(M)SOLDER一體