




Note:

1.Material:

- 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: Copper alloy,t=0.20mm
SELECTIVE GOLD 30u"
- 1.3 Shell: Spcc,t=0.30mm

2.Specification:

- 2.1 Current rating: 1 A Max.
 - 2.2 Dielectric withstanding
voltage: 750 V(ac) for 1 min.
 - 2.3 Contact resistance: 30 mW Max.
 - 2.4 Insulation resistance: 1000 M W Min.
 - 2.5 Total mating force: 7.0 Kgf Max.
 - 2.6 Total unmating force: 1.5 Kgf Min.
 - 2.7 Temperature range: -55°C~85°C
- MATING CYCLES: 3000 CYCLES MIN.

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10	J±0.25	K±0.25
DS-S30-09	30.81	24.99	16.33	7.9	15.0		12.55	2.77	2.84		
DS-S30-15	39.25	33.32	24.66	7.9	15.0		12.55	2.77	2.84		
DS-S30-25	53.04	47.04	38.38	7.9	15.0		12.55	2.77	2.84		
DS-S30-37	69.50	63.50	54.84	7.9	15.0		12.55	2.77	2.84		

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

照片框

ORDER INFORMATION

DS-S30-xx-LF
SERIES | LEADFREE
09~37 WAY
SEMI GOLD 30u"
FEMALE

DESCRIPTION: D-SUB SOLDER FEMALE