





Table 1 Material	
Power Contact	Brass
Metal Shell	Steel/Dimples on Plug only
Insulator	UL94V-0 Thermoplastic 30% glass filled

Table 2 Finish	
Power Contact	Gold-plated
Metal Shell	Nickel plated

Table 3 Electrical Data	
Current Rating	
Power Contact	10 - 40 Amp
Operating Temperature	-55°C - +125°C
Insulator Resistance	Minimum 5000 MΩ
Contact Resistance	Maximum 10mΩ
Dielectric w/standing Volt	1000 V AC per min

Table 4 Dimension & Current Rating		
Current Rating	Dimension	
	øA	øB
40 AMPS	ø3.75	ø4.20
30 AMPS	ø3.20	ø3.65
20 AMPS	ø2.80	ø3.28
10 AMPS	ø1.70	ø2.20

Plug



RoHS Compliant

TOLERANCES ARE

照片框

ORDER INFORMATION

DWD-Pxx-02V2-LF
 SERIES 02V2 LEADFREE
 40:40 AMPS
 30:30 AMPS
 20:20 AMPS
 10:10 AMPS
 MALE

DESCRIPTION: D SUB POWER SERIE 2V2 STRAIGHT DIP TYPE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ± 0.30
 .XX ±
 .XXX ±
 ANG ± 2°