




Table 1 Material	
Power Contact	Brass
Metal Shell	Steel/Dimples on Plug only
Insulator	UL94V-0 Thermoplastic 30% glass filled

Table 2 Finish	
Power Contact	Gold-plated
Metal Shell	Nickel plated

Table 3 Electrical Data	
Current Rating	
Power Contact	10 - 40 Amp
Operating Temperature	-55°C - +125°C
Insulator Resistance	Minimum 5000 MΩ
Contact Resistance	Maximum 10mΩ
Dielectric w/standing Volt	1000 V AC per min

Table 4 Dimension & Current Rating		
Current Rating	Dimension	
	øA	øB
40 AMPS	ø3.75	ø4.20
30 AMPS	ø3.20	ø3.65
20 AMPS	ø2.80	ø3.28
10 AMPS	ø1.70	ø2.20

Socket



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ±
.XXX ±
ANG ± 2°

照片框

ORDER INFORMATION

DWD-Sxx-02V2-LF

SERIES LEADFREE

02V2

40:40 AMPS
30:30 AMPS
20:20 AMPS
10:10 AMPS

FEMALE

DESCRIPTION: D SUB POWER SERIE 2V2 STRAIGHT DIP TYPE