




MATERIAL
Insulator : 30% Glass fiber PBT
Contact Pin : Brass , Gold Flash 6u”

SPECIFICATION
Current Rate : 3 AMP
Insulation Resistance : 5000M Ω Min.
Contact Resistance : 20m Ω Max.
Dielectric Voltage : AC 500V for one minute
Operation Temperature : -40°C to + 105°C
ULNO.E144392

POLES	DIM A	DIM B	POLES	DIM A	DIM B
			21	53.84	50.80
			22	56.38	53.34
3	8.12	5.08	23	58.92	55.88
4	10.66	7.62	24	61.46	58.42
5	13.20	10.16	25	64.00	60.96
6	15.74	12.70	26	66.54	63.50
7	18.28	15.24	27	69.08	66.04
8	20.82	17.78	28	71.62	68.58
9	23.36	20.32	29	74.16	71.12
10	25.90	22.86	30	76.70	73.66
11	28.44	25.40	31	79.24	76.20
12	30.98	27.94	32	81.78	78.74
13	33.52	30.48	33	84.32	81.28
14	36.06	33.02	34	86.86	83.82
15	38.60	35.56	35	89.40	86.36
16	41.14	38.10	36	91.94	88.90
17	43.68	40.64	37	94.48	91.44
18	46.22	43.18	38	97.02	93.98
19	48.76	45.72	39	99.56	96.52
20	51.30	48.26	40	102.1	99.06

F-DG06-1Xxx-LF
Gold Flash 6u”
LEADFREE

RoHS Compliant



煜倫股份有限公司

PART NO. F-DG06-1Xxx									
DWG NO. F-DG06-1Xxx		APPROVED BY CY		TOLERANCES ARE .X ± 0.3 .XX ± 0.2 .XXX AWG	DESCRIP TION:		FEMALE HEADER 2.54*2.54mm STRAIGHT TYPE, SINGLE ROW HEIGHT 8.5mm		
FILE NO.		DRAWING BY							
UNIT / mm	SCALE 1:1	PROJECTION			AREA		REVISIONS	HK	DATE