

### SPECIFICATION

1. INSULATION RESISTANCE : DC 500V 500MΩ 以上
2. VOLTAGE WITHSTANDING : AC 1.2KV 1 min.
3. CONTACT RESISTANCE : AC 1000V 20mΩ MAX.(使用測具0.8 ±0.01)
4. INSERTION FORCE : 0.5Kg~3Kg  
WITHDRAWAL FORCE : 0.3Kg~3Kg
5. FREQUENCY RANGE: 50MHz TO 850 MHz
6. TIGHTEN HEX NUT DOWN TO 4.5 IN-LBS.±0.5 IN-LBS
7. BODY TO BRACKET CLINCH MUST BE ABLE TO WITHSTAND 7.5 IN-LBS.OF TORQUE MIN
8. THE INSULATOR MUST NOT DEFORM OR DISCOLOR WHEN EXPOSED TO TEMPERATURES OF 200°C FOR 5 SECS.AND 170°C FOR 30 SECS.
9. 絕緣套管膠料採用UL認證的

### MATERIALS AND FINISHES

NO	DESCRIPTION	Q'TY	ITEM NO.	MATERIAL	PLATING
1	BODY	1	F-P2215-9A-ROHS	BRASS	NICKEL
2	DIELECTRIC 1	1	T-070153	TEFLON	-
3	DIELECTRIC 2	1	T-070128	TEFLON	-
4	CENTER PIN	1	F-P2215-9A-ROHS	BRASS	GOLD

F-JE17SF-75-LF  
LEADFREE  
RoHS Compliant

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO. F-JE17SF-75

DWG NO. F-JE17SF-75

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

焯倫股份有限公司