

PIN OUT

S1		S2	S1		S2
1	RED	1	14		14
2		2	15		15
3		3	16		16
4		4	17		17
5		5	18		18
6		6	19		19
7		7	20		20
8		8	21		21
9		9	22		22
10		10	23		23
11		11	24		24
12		12	25		25
13		13	26		26

***CONSTRUCTION:

1.CABLE: * UL2651 28AWG*26C PITCH=1.27mm GRAY JACKET.

***CONNECTORS:

2.IDC SOCKET: * IDC 26PIN SOCKET WITH POLARIZED.
* CONTACT: GOLD PLATED.
* INSULATOR: BLACK COLOR PITCH: 2.54mm.
* PLASTIC STRAIN RELIEF.

3.TEST: * CT: 2 ohm IS: 5M ohm.

4.PACKING: * PACK EACH CABLE IN A POLY BAG.

5.MATERIAL: * MATERIAL WITH RoHS GRADE.



PART NO. F2X2-2626-F5C

DWG NO. F2X2-2626-F5C

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

AWG

DESCRIP TION:

TITLE: IDC SOCKET 26PIN FEMALE TO FEMALE

AREA

REVISIONS

HK

DATE

煜倫股份有限公司