

PIN OUT

S1	S2
1	RED
2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	

S1	S2
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	

***CONSTRUCTION:

1.CABLE: * UL2651 28AWG*26C PITCH=1.27mm GRAY JACKET.

***CONNECTORS:

2.IDC SOCKET: * IDC 26PIN SOCKET WITH POLARIZED.
* CONTACT: GOLD PLATED.
* INSULATOR: BLACK COLOR PITCH: 2.54mm.
* PLASTIC STRAIN RELIEF.

3.FERRITE CORE: * RH: B29 FPL 23.8*12*6.3mm.

4.TEST: * CT: 2 ohm IS: 5M ohm.

5.PACKING: * PACK EACH CABLE IN A POLY BAG.

6.MATERIAL: * MATERIAL WITH RoHS GRADE.

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO.F2X2-2626FC-F15C3

DWG NO. F2X2-2626FC-F15C3

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

AWG

DESCRIPTION: IDC SOCKET 26PIN FEMALE TO FEMALE

AREA

REVISIONS

HK

DATE

煜倫股份有限公司