


NOTE:

1. 一般導通測試.
2. 包裝箱須貼UL標籤.



7	热缩管	黑色热缩管 ϕ 1.0mm L=30MM L=5MM	各1	PCS
6	端子	端子, 磷青铜镀锡, WST I12501PS-2	5	PCS
5	HSG	白色 5PIN HSG1.25MM, WST P5-I12501	1	PCS
4	PE	LD-PE 透明料	3	G
3	PVC	白色 PVC	8	G
2	USB	MICRO USB 5PIN B型焊线式公头一体式 黑胶芯	1	PCS
1	线材	USB2.0 CABLE 28#*1P+26#*2C+AL OD:4.32MM 裁线L=480MM	1	PCS
序号	名称	规格描述	用量	单位

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X, $\pm$
.X $\pm$
.XX $\pm$
.XXX $\pm$
ANG $\pm$

照片框

ORDER INFORMATION

FHMIB-055B2628-A45C-LF

SERIES

LEADFREE

450mm

FEMALE TO MALE

26/28 AWG

5 PIN TO 5 PIN B TYPE

DESCRIPTION: