

P1	1	WHITE	1	P2
	2	WHITE	2	
	3	WHITE	3	
	4	WHITE	4	
	5	WHITE	5	
	6	WHITE	6	
	7	WHITE	7	

WIRING TABLE

Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 K Ω)
3. At DC = 300V , Insulation Resistance : 20 M Ω Min.
4. Test Condition : Temperature : 25 $\pm$ 5 $^{\circ}$ C , Humidity : 50% RH Max.

3	50079-8000/Molex	SOCKET CONTACT	14 PCS
2	51021-0700/Molex	HOUSING, 7-POS., 1.25mm PITCH, WHITE	2 PCS
1	Spec./Rei Hsing	WIRE, 26 AWG, UL 10368, HALOGEN FREE	A/R
ITEM	PART NO./SUPPLIER	DESCRIPTION	Q'TY

FHX2-070726MX-F24C-HF
HALOGEN FREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO.FHX2-070726MX-F24C-HF

DWG NO. FHX2-070726MX-F24C-HF

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X. $\pm$
.X $\pm$
.XX $\pm$
.XXX $\pm$
ANG

DESCRIPTION:

AREA

REVISIONS

DATE

煜倫股份有限公司