




					UL NO.: E254391						
SYMBOL	P	W	SP	M	A	TL	T	S1	S2	S3	S4
PANGE	1.0	29	27	1.0	0	2591	0.3	3	3	5	5
TOLERANCE	±0.08	±0.12	±0.1	±0.15	<0.5	±10.0	±0.05	±1.0	±1.0	±1.0	±1.0
CONDUCTOR SPECIFICATION	Tin Properties Copper wire (Tin 2~5u)		THICKNESS (Ct)		0.05		±0.01				
			WIDTH (Cw)		0.65		±0.03				

FPA-CA28-8F5-LF
LEADFREE
RoHS Compliant

Cable Properties (UL STYLE:AWM 20624)

ITEM	Condition	Properties
Conductor Resistance	JTS C-3102 (@20°C)	Less than 1.82OHM/m
Insulation Resistance	DC 500V	More than 1.000OHM/m
Dielectric Strength	AC 500V 1min	No Breakdown
Heat Resistance	85°Cx95Hr	A-2,A-3 Pass
Heat Cycle Test (12Hr2Cycle)	-40°C — 25°C — 85°C — 25°C	A-2,A-3 Pass
Moisture Resistance	40°C,95%RH,96Hrs	A-2,A-3 Pass
Flame Test	UL Sub.758	VW-1 Pass
Flexing Test	180°C Folding Test	More than 20 times
Pull-out Test		More than 20 times
Abrasion Test	ø5mm,600g,60cycle/min	More than 10,000 times
Elongation of Insulation	JIS K-6732	More than 60%

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. FPA-CA28-8F5

DWG NO. FPA-CA28-8F5

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIP TION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司