



FPA-CB06-200-LF
LEADFREE
RoHS Compliant

Insulation: Flame Retardant Polyester
Color: White
Conductor: Copper with 1u m min. tin-Plating
Supporting Tape: Flame Retardant Polyester
Color: Blue

包材	纸箱 K=K 11.6"*9.6"*9.6" 环保ROHS/REACH	1/6000	PCS
	PE袋10.5"*13.5" 有环保标示 环保ROHS/REACH	1/1000	PCS
	纸板A=A 13.2"*9.8" 环保ROHS/REACH	1/1000	PCS
	纸带 15*0.1" 环保ROHS/REACH	0.00006	Kg
4	FFC-ST-0.225*12 环保ROHS/REACH	7	mm
3	FFC-CN-0.035*0.65 环保ROHS/REACH	0.242697	g
2	FFC-FD-0.043*120 环保ROHS/REACH	W=7 L=196	mm
1	FFC-FM-0.043*120 G=NS 环保ROHS/REACH	W=7 L=196	mm
序号	品 名/规 格	用量	单位


 MORETHANALL
 CONNECTORS
 ASSEMBLIES
 煜倫股份有限公司

PART NO. FPA-CB06-200		TOLERANCES ARE X. ± .X ± .XX ± .XXX ± ANG		DESCRIPTION:			
DWG NO. FPA-CB06-200		CHECKED BY CY					
FILE NO.		DRAWING BY					
UNIT / mm	SCALE 1:1	PROJECTION 	AREA	REVISIONS		DATE	