




Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	5
P	Pitch(间距)	1.25±0.10
TP	Total Pitch(总间距)	5.0±0.15
W	Width(总宽度)	7.5±0.15
M	Margin(边缘宽度)	1.25±0.20
L	Total Length(总长度)	35±2
ST	FFC Body Thickness(线身厚度)	0.220±0.030
S1/S2	Conductor Strip Length(裸铜长度)	3/3±0.5
Cw	Conductor Width(导体宽度)	0.80±0.03
Ct	Conductor Thickness(导体厚度)	0.100±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.060±0.005
A1	Slanting(线口倾斜度)	<0.5

ELECTRICAL CHARACTERISTICS
Conductor Resistance: JISC-3102(at20℃) 2.20Ω/M Max.
Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.
Dielectric Strength: Apply AC 500V for one minute.
Continuity Test: Apply microtest machine No Open/Short
Rated voltage & temperature:UL20624 60V 80℃

Material
Insulation: Flame Retardant Polyeste
Color: White
Conductor: Copper with 1u m min.tin-Plating
Supporting Tape: Flame Retardant Polyester
Color: Blue

包装方式:线材每50PCS中间用纸带包好, 30把装1PE袋(需整齐排好),
然后把装好1PE袋的产品用纸板固定好, 10袋装一纸箱.
批量不够15000PCS可自行选择合适纸箱

FPB-CD05-035-LF
LEADFREE
RoHS Compliant

包材	纸箱 K=K 11.6" *9.6" *9.6" 环保ROHS	1/15000	PCS
	PE袋10.5" *13.5" 有环保标示 环保ROHS	1/1500	PCS
	纸板A=A 13.2" *9.8" 环保ROHS	1/1500	PCS
	纸带 15*0.1" 环保ROHS	0.000006	Kg
3	FFC-CN-0.100*0.80 环保ROHS	0.12446	g
2	FFC-FD-0.060*120 环保ROHS	W=7.5 L=29	mm
1	FFC-FM-0.060*120 G-NS 环保ROHS	W=7.5 L=29	mm
序号	品名/规格	用量	单位

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. FPB-CD05-035

DWG NO. FPB-CD05-035

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIP TION:

AREA

REVISIONS

HK

DATE