



Conductor Resistance: JISC-3102(at20℃) 2.20 Ω/M Max.
Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.
Dielectric Strength: Apply AC 500V for one minute.
Continuity Test: Apply microtest machine No Open/Short
Rated voltage & temperature:UL20624 60V 80℃

Insulation: Flame Retardant Polyeste
Color: White
Conductor: Copper with 1u m min.tin-Plating
Supporting Tape: Flame Retardant Polyester
Color: Blue

包装方式:线材每50PCS两端用纸带包好,30把装1PE袋(需整齐排好),然后把装好1PE袋的产品用纸板固定好,6袋装一纸箱。
批量不够9000PCS可自行选择合适纸箱

包材	纸箱 K=K 11.6" *9.6" *9.6" 环保 RoHS/REACH	1/9000	PCS
	PE袋10.5" *13.5" 有环保标示 环保 RoHS/REACH	1/1500	PCS
	纸板A=A 13.2" *9.8" 环保 RoHS/REACH	8/9000	PCS
	纸带 15*0.1" 环保 RoHS/REACH	0.000006	Kg
4	FFC-ST-0.225*12 环保 RoHS/REACH	16.5	mm
3	FFC-CN-0.035*0.32 环保 RoHS/REACH	0.4779264	g
2	FFC-FD-0.043*120 环保 RoHS/REACH	W=16.5 L=150	mm
1	FFC-FM-0.043*120 G-NS 环保 RoHS/REACH	W=16.5 L=142	mm
序号	品 名/规 格	用量	单位

PART NO. FPV-CA32-150

DWG NO. FPD-CA32-150

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

	X. ±
	.X ±
	.XX ±
	.XXX ±
	ANG

DESCRIPTION:

AREA

REVISIONS

DATE

煜倫股份有限公司