

Symbol 标号	Item 项目	Specification 规格
N	No.of Conductors(导体芯数)	33
P	Pitch(间距)	0.50±0.05
TP	Total Pitch(总间距)	16.0±0.10
W	Width(总宽度)	17.0±0.10
M	Margin(边缘宽度)	0.5±0.1
L	Total Length(总长度)	76±3
T	Insertion Thickness(插入厚度)	0.303±0.050
ST	FFC Body Thickness(线身厚度)	0.121±0.030
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1
B1/B2	Supporting tape Length(补强板长度)	6/6±2
Cw	Conductor Width(导体宽度)	0.32±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

FPV-CB33-076-LF
LEADFREE
RoHS Compliant

ELECTRICAL CHARACTERISTICS
Conductor Resistance: JISC-3102(at20℃) 2.20Ω/M Max.
Insulation Resistance: Apply the voltage of DC 500V for one minute 100MΩ Min.
Dielectric Strength: Apply AC 500V for one minute.
Continuity Test: Apply microtest machine No Open/Short
Rated voltage & temperature:UL20624 60V 80℃

Material
Insulation: Flame Retardant Polyeste
Color: White
Conductor: Copper with lu m min.tin-Plating
Supporting Tape: Flame Retardant Polyester
Color: Blue

包装方式:线材每50PCS两端用纸带包好,30把装1PE袋(需整齐排好),
然后把装好1PE袋的产品用纸板固定好,10把装一纸箱.
批量不够15000PCS可自行选择合适纸箱

序号	品 名/规 格	用量	单位
包材	纸箱 K=K 11.6"*9.6"*9.6" 环保ROHS	1/15000	PCS
	PE袋10.5"*13.5" 有环保标示 环保ROHS	1/1500	PCS
	纸板A=A 13.2"*9.8"环保ROHS	1/1500	PCS
	纸带 15*0.1"环保ROHS	0.1	Kg
4	FFC-ST-0.225*12 环保ROHS	17.0	mm
3	FFC-CN-0.035*0.32 环保ROHS	0.36143184	g
2	FFC-FD-0.043*120 环保ROHS	W=17.0 L=76	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=17.0 L=76	mm

MORETHANALL CONNECTORS ASSEMBLIES
煜倫股份有限公司

PART NO. FPV-CB33-076			
DWG NO. FPV-CB33-076	CHECKED BY CY	TOLERANCES ARE .X ± .XX ± .XXX ± AWG	DESCRIP TION:
FILE NO.	DRAWING BY		
UNIT / mm	SCALE 1:1	PROJECTION	AREA / REVISIONS / HK / DATE