

J

I

H

G

F




E

D

C

B

A



ELECTRICAL CHARACTERISTICS

Conductor Resistance: JISC-3102(at20℃) 2.20 Ω /M Max.

Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.

Dielectric Strength: Apply AC 500V for one minute.

Continuity Test: Apply microtest machine No Open/Short

Rated voltage & temperature:UL20624 60V 80℃

Material

Insulation: Flame Retardant Polyeste

Color: White

Conductor: Copper with 1u m min.tin-Plating

Supporting Tape: Flame Retardant Polyester

Color: Blue

Symbol 标号	Item 项目	Specification 规格
N	No.of Conductors(导体芯数)	33
P	Pitch(间距)	0.50±0.05
TP	Total Pitch(总间距)	16.0±0.10
W	Width(总宽度)	17.0±0.10
M	Margin(边缘宽度)	0.5±0.1
L	Total Length(总长度)	200±5
T	Insertion Thickness(插入厚度)	0.303±0.050
ST	FFC Body Thickness(线身厚度)	0.121±0.030
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1
B1/B2	Supporting tape Length(补强板长度)	6/6±2
Cw	Conductor Width(导体宽度)	0.32±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

包装方式:线材每50PCS两端及中部用纸带包好,4把装1PE袋(需整齐排好),
然后把装好1PE袋的产品用纸板固定好,5把装一纸箱。
批量不够1000PCS可自行选择合适纸箱

FPV-CB33-200-LF

LEADFREE

RoHS Compliant

包材	C型纸箱 K=K 15.7"*13.3"*8.6" 环保ROHS	1/1000	PCS
	PE袋12"*17" 有环保标示 环保ROHS	1/200	PCS
	纸板A=A 14.9"*12.1" 环保ROHS	1/200	PCS
	纸带 15*0.1" 环保ROHS	0.000006	Kg
4	FFC-ST-0.225*12 环保ROHS	17.0	mm
3	FFC-CN-0.035*0.32 环保ROHS	1.642872	g
2	FFC-FD-0.043*120 环保ROHS	W=17.0 L=196	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=17.0 L=196	mm
序号	品 名 / 规 格	用 量	单 位



PART NO. FPV-CB33-200

DWG NO. FPV-CB33-200

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

ANG

DESCRIP TION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司