




Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	40
P	Pitch(间距)	0.50±0.05
TP	Total Pitch(总间距)	19.50±0.10
W	Width(总宽度)	20.50±0.10
M	Margin(边缘宽度)	0.5±0.1
L	Total Length(总长度)	70±3
T	Insertion Thickness(插入厚度)	0.303±0.050
ST	FFC Body Thickness(线身厚度)	0.121±0.030
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1
B1/B2	Supporting tape Length(补强板长度)	6/6±2
Cw	Conductor Width(导体宽度)	0.32±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

ELECTRICAL CHARACTERISTICS

Conductor Resistance: JISC-3102(at20℃) 2.20Ω/M Max.

Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.

Dielectric Strength: Apply AC 500V for one minute.

Continuity Test: Apply microtest machine No Open/Short

Rated voltage & temperature:UL20624 60V 80℃

Material

Insulation : Flame Retardant Polyeste

Color : White

Conductor : Copper with 1u m min.tin-Plating

Supporting Tape : Flame Retardant Polyester

Color : Blue

4	FFC-ST-0.225*12 环保ROHS	20.5	mm
3	FFC-CN-0.035*0.32 环保ROHS	0.39428928	g
2	FFC-FD-0.043*120 环保ROHS	W=20.5 L=70	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=20.5 L=70	mm
序号	品名/规格	用量	单位

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

FPV-CB40-070-LF
SERIES 70mm LEADFREE
40 WAY
BOTH SIDES
FPC CABLE

DESCRIPTION: