




P. C. B . LAYOUT



A: 11.54 mm

B: 6.00 mm

C: 3.00 mm

MATERIAL

HOUSING :PBT, UL-94V0

CONTACT :COPPER ALLOYS

PLATED :GOLD FLASH

COLOR :BLACK

SPECIFICATION

CURRENT : 3A

OPERATING TEMPERAURE : -55° C TO $+105^{\circ}$ C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE: 1000 MEGAOHMS MIN

WITHSTAND VOLTAGE : 1000 V AC/minute

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. $\pm$
.X ± 0.38
.XX ± 0.25
.XXX $\pm$
ANG $\pm 5^{\circ}$

照片框

ORDER INFORMATION

H-D-2X05E2-LF
SERIES | LEADFREE
10 WAY
DIP 180°

DESCRIPTION: PH2.54 180° H:2.54 2*5(N2)PIN