



Recommended P.C.B Layout

**MATERIAL**

Insulator : 30% Glass fiber PBT  
Contact Pin : Brass

**SPECIFICATION**

Current Rate : 3 AMP  
Insulation Resistance : 5000MΩMin. at DC 500V  
Contact Resistance : 20mΩMax. at DC 100mA  
Dielectric Voltage : AC 500V for one minute  
Operation Temperature : -40°C to + 105°C

| POLES | DIM E | POLES | DIM E  |
|-------|-------|-------|--------|
|       |       | 26    | 63.50  |
| 2     | 2.54  | 27    | 66.04  |
| 3     | 5.08  | 28    | 68.58  |
| 4     | 7.62  | 29    | 71.12  |
| 5     | 10.16 | 30    | 73.66  |
| 6     | 12.70 | 31    | 76.20  |
| 7     | 15.24 | 32    | 78.74  |
| 8     | 17.78 | 33    | 81.28  |
| 9     | 20.32 | 34    | 83.82  |
| 10    | 22.86 | 35    | 86.36  |
| 11    | 25.40 | 36    | 88.90  |
| 12    | 27.94 | 37    | 91.44  |
| 13    | 30.48 | 38    | 93.98  |
| 14    | 33.02 | 39    | 96.52  |
| 15    | 35.56 | 40    | 99.06  |
| 16    | 38.10 | 41    | 101.60 |
| 17    | 40.64 | 42    | 104.14 |
| 18    | 43.18 | 43    | 106.68 |
| 19    | 45.72 | 44    | 109.22 |
| 20    | 48.26 | 45    | 111.76 |
| 21    | 50.80 | 46    | 114.30 |
| 22    | 53.34 | 47    | 116.84 |
| 23    | 55.88 | 48    | 119.38 |
| 24    | 58.42 | 49    | 121.92 |
| 25    | 60.96 | 50    | 124.46 |



焯倫有限公司

PART NO. H-D136-2Xxx

DWG NO. H-D136-2Xxx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.3  
.XX ± 0.2  
.XXX  
AWG

DESCRIPTION:  
AREA

PIN HEADER 2.54\*2.54mm  
STRAIGHT TYPE, DUAL ROWS  
REVISIONS  
HK  
DATE