



FIMISH  
 .CONTACT:15u INCH GOLD PLATOD  
 OTHER  
 .ROHS REGULATION COMPLY  
 .Cd & Pb CONTENT FOR BRASS SHOULD BE LESS  
 THAN THE FOLLOWING VALUE  
 Cd<75 PPM Pb<40,000 PPM

MATERIAL  
 Insulator : 30% Glass fiber PBT  
 Contact Pin : Brass

SPECIFICATION  
 Current Rate : 3 AMP  
 Insulation Resistance : 5000MΩMin. at DC 500V  
 Contact Resistance : 20mΩMax. at DC 100mA  
 Dielectric Voltage : AC 500V for one minute  
 Operation Temperature : -40°C to + 105°C

FIMISH  
 Contact:15u" Inch gold plated

PART NUMBER	POLES	DIM E	POLES	DIM E
H-RG15-2X05	2	2.54	21	50.80
	3	5.08	23	55.88
	4	7.62	24	58.42
	5	10.16	25	60.96
	6	12.70	26	63.50
	7	15.24	27	66.04
	8	17.78	28	68.58
	9	20.32	29	71.12
	10	22.86	30	73.66
	11	25.40	31	76.20
	12	27.94	32	78.74
	13	30.48	33	81.28
	14	33.02	34	83.82
	15	35.56	35	86.36
	16	38.10	36	88.90
	17	40.64	37	91.44
	18	43.18	38	93.98
	19	45.72	39	96.52
	H-RG15-2X20	20	48.26	40



PART NO. H-RG15-2Xxx

DWG NO. H-RG15-2Xxx

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE  
 .X ± 0.3  
 .XX ± 0.2  
 .XXX  
 AWG

DESCRIPTION:	PIN HEADER 2.54*2.54mm RIGHT ANGLE TYPE, DUAL ROWS			
	AREA	REVISIONS	HK	DATE

煜倫股份有限公司