



Recommended P.C.B Layout

MATERIAL $\triangle B$

Insulator: NY6T UL94-V0
Contact Pin : Brass

SPECIFICATION

- $\triangle B$ Current Rate : 8 AMP PER PIN(20AWG)
- Insulation Resistance : 5000M Ω Min. at DC 500V
- Contact Resistance : 20m Ω Max. at DC 100mA
- Dielectric Voltage : AC 500V for one minute
- $\triangle B$ Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION \rightarrow

X. \pm
.X \pm 0.30
.XX \pm 0.20
.XXX \pm
ANG \pm 3°

照片框

ORDER INFORMATION

H-V38X107C-2X08-LF
SERIES | | | | LEADFREE
180°SMT | | | | CAP 16 WAY
NON POST CONTACT 10.7mm
HIGH 3.8mm

DESCRIPTION: PIN HEADER 2.54*2.54mm SMT S/T TYPE, DUAL ROWS CAP+T R