



Specifications:
 Current Rating:3.0A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:20m ohm. Max.
 Insulation Resistance:1,000M ohm. Min.
 Withstanding Voltage:500V AC For One Minute
 Operating Temperature Range:-40°C To +105°C

Material and Finish
 Insulator:Nylon 6T (UL94V-0)
 Insulator Color:Black
 Contact:Brass
 Plating: Tin

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X ±
 .X ± 0.20
 .XX ± 0.15
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

H25S-D1273030T-1Xxx-LF

SERIES

LEADFREE

1X01:01 WAY

1X40:40 WAY

DIP180°
 TOTAL 12.7mm

TIN
 DIP 3.0mm
 CONTACT 3.0mm

DESCRIPTION:2.50mm Pin Header Single Row&Double Insulator Straight Type