



Recommended P.C.B.Layout

**MATERIAL**

Insulator: LCP UL94-V0  
Contact Pin: Brass

**SPECIFICATION**

Current Rate : 3 AMP  
Insulation Resistance : 5000MΩMin. at DC 500V  
Contact Resistance : 20mΩMax. at DC 100mA  
Dielectric Voltage : AC 500V for one minute  
Operation Temperature: -40°C to +105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ± 3°

照片框

**ORDER INFORMATION**

H39-D31114045-1X08-LF  
SERIES | | | | LEADFREE  
| | | | 08 WAY  
| | | | DIP 4.50mm  
| | | | CONTACT 11.40mm  
| | | | BASE 3.18mm  
| | | | DIP 180°

DESCRIPTION: PIN HEADER 3.96mm H=3.18 W=6.35 SINGLE ROW, STRAIGHT TYPE