



RECOMMENDED PCB LAYOUT(B1 Type)

### Technical Data :

Insulator Material: PA6T, UL 94V-0  
 Color:black  
 Contact : 1.14x1.14mm  
 Contact Material: Brass  
 Plating: Tin plated  
 Current Rating : 8.2Amp 30°C Temperature Rise  
 Insulator resistance : 1000 Megohms min.  
 Dielectric withstanding : AC 500V for 1 Minute  
 Operating Temperature: -40°C to +105°C.  
 Max. processing Temp: 230°C for 30-60 seconds.  
 260°C for 10 seconds.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20

DATE

.XXX ±

ANG ± 3°

照片框

ORDER INFORMATION

H51-V51X080C-1X02R-LF  
 SERIES | | | | | LEADFREE  
 180°SMT | | | | | R TYPE FOOT  
 HIGH 5.08mm | | | | | CAP | 02 WAY  
 NON POST | | | | | CONTACT 8.0mm

煜倫股份有限公司

www.morethanall.com

SIZE A4

PPOJECTION

DESCRIPTION: PH3.96 SMT"B" H=3.18W=6.35 CAP+T/R