



SPECIFICATIONS

Material

Insulator : PBT glass reinforced, rated UL94V-0

Contact : Phosphor Bronze

Strain Relief Hook : Phosphor Bronze

Matching requirements

Wire : Flat ribbon cable pitch 0.635mm 30AWG

Insertion Depth : 2.60mm to 3.10mm

Lead Size Accepted : 0.40mm square

Electrical

Current Rating : 1 Amp

Contact Resistance : 30m ohm Max.

Insulator Resistance : 1000M ohm min.

Dielectric Withstanding Voltage : 250V AC for 1 minute

Operating Temp Range : -40°~+105°C

Pos.

06 08 10 12 14 16 20 24

26 30 34 40 44 50 60 68 80

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

HAF-C3A-xxx-LF
SERIES | LEADFREE
006~080WAY
A TYPE
IDC THREE TYPE

DESCRIPTION: Micro IDC Socket Pitch 1.27mm*1.27mm