



P.C.B LAYOUT

Technical Data

Material:

Pin(outer sleeve): Brass, machined  
 CuZn38Pb2

Plating(outer sleeve):

Tin Plated:  $2\mu\text{m}/80\mu\text{''NI}$ ,  $5\mu\text{m}/200\mu\text{''Sn}$

Gold Plated:  $2\mu\text{m}''/80\mu\text{''Ni}$ ,  $0.8\mu\text{''}$  gold

Plating(Contact):  $2\mu\text{m}/80\mu\text{''NI}$ , gold or Tin plated

Insulator: pps UL94V-0

Clip(Contact 4 Finger): Beryllium copper, heat treated

Electrical:

Current rating: 3Amps/contact max.

Contact resistance:  $\leq 4\text{m}\Omega$ /contact

Insulation resistance:  $\geq 1000\text{M}\Omega$  at  $V=100\text{V}$

Operating voltage: 60VAC/DC

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X,  $\pm$   
 .X  $\pm 0.30$   
 .XX  $\pm 0.20$   
 .XXX  $\pm 0.15$   
 ANG  $\pm$

照片框

ORDER INFORMATION

HASP-Dx-1Xxx-LF

SERIES

LEADFREE

1X02:02 WAY

1X50:50 WAY

G: GOLD

T: TIN

DIP 180°

DESCRIPTION: