



P.C.Board Layout
TOLERANCE: ±0.05

Material:

Housing: PA9T, UL94V-0, Black.

Contacts: High conductivity copper, Gold Plated on Contact Area and 100u" Tin Plated on Solder Tail over 80u" Nickel.

Lock: Brass, 100u" Tin Plated over 40u" Nickel.

Electrical Characteristics:

Current Rating: 5 AMP.

Dielectric Withstanding Voltage: AC 500V.

Insulation Resistance: 1000MΩ min.

Contact Resistance: 25mΩ max.

Operating Temperature: -55°C~+125°C.

***RoHS Compliant**

Positions	A	B	C
02	7.56	5.69	6.29
03	8.83	6.96	7.56
04	10.10	8.23	8.83
06	12.64	10.77	11.37
08	15.18	13.31	13.91
10	17.72	15.85	16.45
12	20.26	18.39	18.99

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.35
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

HAUA-PW31P-xx-LF

SERIES

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

|

LEADFREE
02~12 WAY
POST
UNMATED LONG 3.1mm
90°SMT
MALE

DESCRIPTION: 1.27mm SMC Male Connector Single Row Right Angle SMD Type