



Specifications

Current Rating:1.1Amp
 Insulation Resistance:10000MΩMin.
 Dielectric Withstanding Voltage:500VAC
 Contact Resistance:10mΩMax.
 Operating Temperature:-55°C to +125°C
 Materials

Contact Material:Phosphor Bronze
 Insulator Material:High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material

hazardous substances control standards.
 "★":Critical Characteristics, indicates product characteristics, functionalities,and manufacturing processes regarding to customer's specifications

No. of PIN/ROW	Dimension Information			
	A	B	C	D
2x6	6.35	8.37	9.37	14.71
2x10	11.43	13.45	14.45	19.79
2x13	15.24	17.26	18.26	23.60
2x16	19.05	21.07	22.07	27.41
2x20	24.13	26.15	27.15	32.49
2x25	30.48	32.50	33.50	38.84
2x34	41.91	43.93	44.93	50.27
2x40	49.53	51.55	52.55	57.89

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

HAUB-SFL-xxx-LF
 SERIES | LEADFREE
 | 012-080 WAY
 | LOCK
 | IDC
 | FEMALE

DESCRIPTION: IDC Female Connector Type B with Locking Latches