

Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.20mm.
- 1.3 Shell: Cold rolled steel,t=0.40mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel,tin or gold plated

|     |             |       |                   |                     |                  |
|-----|-------------|-------|-------------------|---------------------|------------------|
| 6   | 8.0 Nut     | 2     | Brass             | H4.75*8.0           | Nickel Plated    |
| 5   | 3B Nut      | 2     | Brass             | H4.75*4.75          | Nickel Plated    |
| 4   | Back-shell  | 1     | Cold Rolled Steel | T=0.40mm            | Tin Plated       |
| 3   | Front-shell | 1     | Cold Rolled Steel | T=0.40mm            | Nickel Plated    |
| 2   | Contact     | 15~62 | Brass             | T=0.20mm            | Gold Flashed     |
| 1   | Housing     | 2     | P.B.T             | UL 94-V0            | Black/Blue/White |
| No. | Part Name   | Q'ty  | Material          | Remarks & Thickness | Finish           |

| PART NO  | A±0.25 | B±0.25 | C±0.25 | D±0.25 | E±0.25 | G±0.25 | H±0.20 | I±0.20 |
|----------|--------|--------|--------|--------|--------|--------|--------|--------|
| HDC-P-26 | 39.20  | 33.32  | 25.25  | 8.30   | 16.00  | 12.60  | 2.29   | 3.96   |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±  
.X±  
.XX±  
.XXX±  
ANG±

PPOJECTION



ORDER INFORMATION

HDC-P-26-LF  
SERIES | LEADFREE  
26 WAY  
MALE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com