



Materials:

- \* Insulator: Glass filled polyester UL 94V-0
  - \* Contacts: Copper alloy
  - △ \* Shell: Steel, Nickel plated as standard
- Recommended P.C. Board Layout see drawing No. CD0304S\*

Circuits	Dimension				
	A	B	C	D	E
15	25.00(.984)	30.8(1.213)	16.92(.666)	19.2(.756)	2.29(.090)
26	33.32(1.312)	39.2(1.543)	25.25(.994)	27.70(1.091)	2.29(.090)
44	47.04(1.852)	53.1(2.091)	38.96(1.534)	41.10(1.618)	2.29(.090)
62	63.50(2.500)	69.4(2.732)	55.42(2.182)	57.30(2.256)	2.41(.095)

Mounting Style				
Code		Code J	Code N	Code Z
		DIM. L= 4.0mm	DIM. L= 4.0mm	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X. ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

HDCD-PGx-xx-LF  
SERIES | | | LEADFREE  
15-62 WAY  
J: JACKSCREW  
N: NUT  
Z: CLIP  
MALE  
GOLD

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: HIGH-DENSITY D-SUB TOP ENTRY HIGH PROFILE BOARD MOUNT MALE CONNECTOR