



Material & Finish

SHELL:

Steel
Zinc plated, Tin plated
or Nickel plated steel

PIN CONTACT:

Phosphor bronze or brass
Gold plated

INSULATOR:

PBT & Glass-fibre reinforced
UL 94V-0

NUMBER OF CONTACT:

15,26,44,62

CURRENT RATING:

5 Amp

DIELECTRIC STRENGTH:

AC 1000V Min. (for one minute)

INSULATOR RESISTANCE:

500MΩ Min. (at 500V DC)

CONTACT RESISTANCE

15mΩ Max. mated

TEMPERATURE:

-55° C to +105° C

Positions

	A	B	C	D	E	P
15	16.92	24.99	30.81	19.28	0.25	2.29
26	25.25	33.32	39.14	27.65	0.51	2.29
44	38.96	47.04	53.04	41.30	0.51	2.29
62	55.42	63.50	69.32	57.44	0.58	2.41

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

HDCD-Px-xx-LF
SERIES | LEADFREE
15-62WAY
S:SEMI GOLD
G:GOLD
MALE

DESCRIPTION:D-SUB P.C.B. HIGH DENSITY STRAIGHT HIGH PROFILE MALE