



SPECIFICATION

SHELL: SPCC.

INSULATOR: PBT .

CONTACT: COPPER ALLOY. STAMPED-PIN

CURRENT RATING: 3 Amps

CONTACT RESISTANCE: 15 mOHMS MAX

INSULATOR RESISTANCE: 1000 MOHMS MIN

VOLTAGE: 500V AC FOR 1 MINUTE

TEMPERATURE: -55°C TO +105°C

PART NO	A	B	C	D
HDCD145-SSZ-15	30.80	24.99	16.34	19.20
HDCD145-SSZ-26	39.20	33.32	24.70	27.70
HDCD145-SSZ-44	53.00	47.04	38.40	41.10
HDCD145-SSZ-62	69.40	63.50	54.80	57.30
HDCD145-SSZ-78	67.00	61.10	52.20	55.10

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ± 0.30
.XX ± 0.25
.XXX ± 0.15
ANG ±

照片框

ORDER INFORMATION

HDCD145-SSZ-xx-LF

SERIES

LEADFREE
15-78 WAY
CLIP
SEMI GOLD
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: