



Material & Finish

SHELL:

Steel
Zinc plated, Tin plated
or Nickel plated steel

PIN CONTACT:

Phosphor bronze or Brass
Gold plated

INSULATOR:

PBT & Glass-fibre reinforced
UL-94-V0

NUMBER OF CONTACT:

15,26,44,62

CURRENT RATING:

2 Amp

DIELECTRIC STRENGTH:

AC 500V Min. (for one minute)

INSULATOR RESISTANCE:

1000MΩ Min. (at 500V DC)

CONTACT RESISTANCE

15mΩ Max. mated

TEMPERATURE:

-55°C to +105°C

Positions

	A	B	C	D	E	P
15	16.92	24.99	30.81	19.28	0.25	2.29
26	25.25	33.32	39.14	27.65	0.25	2.29
44	38.96	47.04	53.04	41.30	0.25	2.29
62	55.42	63.50	69.32	57.44	0.31	2.41

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ± 3°

PJECTION

照片框

ORDER INFORMATION

HDD-Px-xx-LF
SERIES | LEADFREE
15-62WAY
S: SEMI GOLD
G: GOLD
MALE

DESCRIPTION: D-SUB HIGH DENSITY P.C.B. S/T TYPE MALE (15-62)