



Recommended mounting hole pattern
for 3.4mm thick P.C Board

SPECIFICATION

Shell: Steel, Nickel Plated

Insulator: PBT+30% Glass Fiber
UL94-V0, Color Black

Contact: Copper Alloy, Machined Pin
15 Micro-Inches Gold min. Plated
Over Nickel 50 Micro Inches min.

Hexnut: Copper Alloy, Nickel Plated
Torque Requirement On Standoffs: min. 7.2kg/fcm(0.7Nm).

Current Rating: 5 Amps

Contact Resistance: 15 milliohms max

Insulation Resistance: 1000 megohms min.

Dielectric Withstanding Voltage: 500V AC For 1 Minute

Temperature: -50°C to +100°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ± 3°

P PROJECTION

照片框

ORDER INFORMATION

HDD-SGN-104-LF
SERIES | | LEADFREE
| | 104 WAY
| NUT
| FULL GOLD
FEMALE

DESCRIPTION: