



PCB LAYOUT

Material & finish

SHELL:

Steel
Zinc plated, Tin plated
or Nickel plated steel

PIN CONTACT:

Phosphor bronze or brass

INSULATOR:

PBT & Glass-fibre reinforced
UL 94V-0

NUMBER OF CONTACT:

78

CURRENT RATING:

5 Amp

DIELECTRIC STRENGTH:

1000V for one minute

INSULATOR RESISTANCE:

5000M Ω Min. (at 500V DC)

TEMPERATURE:

-55°C to +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. \pm
X \pm 0.30
.XX \pm 0.25
.XXX \pm 0.10
ANG \pm 3°

照片框

ORDER INFORMATION

HDD-SGZJ-78-LF

SERIES | | | | LEADFREE
| | | | 78WAY
| | | | JACKSCRW
| | | | CLIP
| | | | FULL GOLD
| | | | FEMALE

DESCRIPTION: D-SUB HIGH DENSITY P.C.B. STRAIGHT FEMALE BACK RIVET BRACKET FRONT WITH 4.8mm HEX NUT 78Pin