



PC BOARD LAYOUT

- Note:
1. Material:
    - 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
    - 1.2 Contact: Copper alloy,t=0.20mm
    - 1.3 Shell: Spcc,t=0.30mm
  2. Specification:
    - 2.1 Current rating: 1 A Max.
    - 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
    - 2.3 Contact resistance: 30 OHM Max.
    - 2.4 Insulation resistance: 1000 OHM Min.
    - 2.5 Total mating force: 8.0 Kgf Max.
    - 2.6 Total unmating force: 1.5 Kgf Min.
    - 2.7 Temperature range: -55°C-85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I ±0.20		
HDD-SSJ-15	30.81	24.99	16.33	7.9	16.0		12.55	2.29	3.96		
HDD-SSJ-26	39.25	33.32	24.66	7.9	16.0		12.55	2.29	3.96		
HDD-SSJ-44	53.04	47.04	38.38	7.9	16.0		12.55	2.29	3.96		
HDD-SSJ-62	69.50	63.50	54.84	7.9	16.0		12.55	2.41	3.96		

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ± 0.10  
ANG ±

PJECTION

照片框

ORDER INFORMATION

HDD-SSJ-xx-LF  
SERIES | LEADFREE  
| 15-62WAY  
| JACKSCRW  
| SEMI GOLD  
| FEMALE

DESCRIPTION: HIDDEN D-SUB 前鉗型 (不通孔)

煜倫股份有限公司

www.morethanall.com