




RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(G)

NOTES

- MATERIAL:**
Housing:PBT, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Boardlock:Copper Alloy.
- FINISH:**
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Ared.
Shell:Tin Plated.
Boardlock:Tin Plated.
- This Product is LEAD-FREE & RoHS Compliance Product.

SPECIFICATIONS

- D-SUB
- Voltage: 250 VAC(RMS) Max.
- Current Rating: 3 Ampere per Contact
- Contact Resistance: 25 Milliohms Max.
- Insulation Resistance: 5000 Megohms Min.
- Dielectric Withstanding Voltage: 1000V AC(RMS)
- Total Mating Force: 6.0 Kgf Max.
- Total Unmating Force: 1.2 Kgf Min.
- Operating Temperature: -55°C to +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ± 0.25
.XXX ± 0.13
ANG ± 2°

照片框

ORDER INFORMATION

HDD-SSZ-15-LF
SERIES | LEADFREE
15 WAY
CLIP
SEMI GOLD
FEMALE

DESCRIPTION: D-SUB 15 FEMALE HIGH DENSITY STRAIGHT DIP