



Note:
 1.Material:
 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
 1.2 Contact: Copper alloy,t=0.20mm
 1.3 Shell: Spcc,t=0.30mm
 2.Specification:
 2.1 Current rating: 1 A Max.
 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
 2.3 Contact resistance: 30 mVMax.
 2.4 Insulation resistance: 1000 MMin.
 2.5 Total mating force: 8.0 Kgf Max.
 2.6 Total unmating force: 1.5 Kgf Min.
 2.7 Temperature range: -55°C~85°C

HDE-Px-xx-LF
 LEADFREE
 S:SEMI-GOLD
 G:FULL-GOLD

RoHS Compliant

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10
HDE-Px-15	30.81	24.99	16.92	8.38	17.0		12.55	2.29	3.96
HDE-Px-26	39.25	33.32	25.25	8.38	17.0		12.55	2.29	3.96
HDE-Px-44	53.04	47.04	38.96	8.38	17.0		12.55	2.29	3.96
HDE-Px-62	69.50	63.50	55.42	8.38	17.0		12.55	2.41	3.96



PART NO. HDE-Px-xx	
DWG NO. HDE-Px-xx	
FILE NO.	
UNIT / mm	SCALE 1:1

APPROVED BY CY	TOLERANCES ARE .X ± 0.3 .XX ± 0.20 .XXX ± 0.100 AWG
DRAWING BY	
PROJECTION	

DESCRIPTION:			
AREA	REVISIONS	HK	DATE

煜倫股份有限公司